MC generation for the B group

- Realistic MC update/remind
- Existing samples summary
- Plan: requested samples
- Developments: SAM-store and filters

Some statistics for summer production (>4.10.0int3):

- Number of official samples: 44
- Number of events simulated: 35,323,897
- No. of events produced and stored to disk: 13,087,953
- Most samples are on CAF server only fcdfdata032
- 12 bigger samples are on DFC, available via dCache.
- List available from web page

http://www-cdf.fnal.gov/internal/physics/bottom/realisticMC/available_samples.html

http://www-cdf.fnal.gov/internal/physics/bottom/realisticMC/available_samples.html

- Follow the links for full information on the sample
- Look also for the filtered samples, when available.

All the above sample produced in Glasgow (cdfg/scotgrid)

Structure of realistic B-MC:

- Step 1
 - Generation (Only Pythia and Bgenerator used to now)
 - Simulation with Silicon clustering

cdfSim

- Step 2
 - Trigger Simulation TRGSim++ 4.9.1hpt3
- Step 3
 - svtfilter or Prereq
 - Production ← Use mcProduction here

Tcl files are produced the same way as in standard MC, but number of events and run number change:

Use script ./multirun.pl with input list of runs.

Input: total number of events, max events per job (Filter included!)

>= 1 job per run number

Tar file available from fcdflnx2/scratch/dauria/jim_submit

Plan:

- Generic samples:
 - At least 2 big samples requested: hadronic and 1+svt details to be defined
- Inclusive samples
 - J/Psi X with Pythia
- Single-channel decay:
 - many samples, including charm. ← charm has low trigger efficiencly.

Developments:

- Smart filters required to improve efficiency
- Use SAM to store files and to make bookeeping. Tests were good. It will improve.
- Move from web page to searchable database.

Problem report:

- QQ decayer has bad behaviour in 4.11.2 for lifetimes
- HepgFilter had limit to pdg < 10000 (excluding D1 (aka 1P10))